

Temperature Monitoring

Technical datasheet



Temperature sensor



sub-GHz radio protocol



Bridge



eSIM



Sensorfact software

TEMPERATURE SENSOR

Measurement	Measuring range Accuracy Measuring frequency Report frequency Trigger for critical data transmission	-40 °C to 85 °C 0.5 °C (-5 °C to 75 °C) Every 3 sec Every 2 min, or directly after measurement if trigger for critical data transmission is reached 2 °C
Battery	Type Expected operating time*	Li-SOCl ₂ , 3.6V Up to 10 years
Enclosure specification	Material IP rating Dimensions	POLYblend 65 FS / TPU IP67 37 x 23 x 14mm
Installation	Ambient temperature Relative humidity Altitude Pollution degree Environment Radio frequency	-40 °C to 85 °C 0 - 100% < 2000m above sea level 4 Indoor use 863-870 MHz / 902-928 MHz
Production details		Produced in Europe
Compliance		RED 2014/53/EU Radio Equipment Regulations 2017, FCC Part 15C, IEC 61010-1:2010

**Depends on measurement frequency, amount of critical data transmissions and ambient temperature.*

BRIDGE

Power specification	Power supply	10-32 VDC, Max. 5W
Network interfaces	Integrated eSIM	Roams freely between all available networks and selects operator based on the best signal strength
Enclosure specification	Case material IP rating Dimensions	Nylon 6/6 IP67 131 x 115 x 33mm
Installation	Operating temperature Environment Radio frequency	-10 °C to 40 °C Indoor use 863-870 MHz (902-928 MHz)
Production details		Produced in Europe
Compliance		RED 2014/53/EU Radio Equipment Regulations 2017, FCC Part 15C, IEC 61010-1:2010